



Outperform every day.™

**Project:**

**Item Number:**

**Quantity:**

**VACUUM SEALING BAGS**



**DESCRIPTION**

Vollrath vacuum bags are Reduced Oxygen Packaging (ROP), not oxygen permissible.

Item No.	Type of Bag	For Use With Type of Machine	Dimensions Inches (CM)	Capacity ①					Max Temp °F (°C)	Mil	Oxygen Transfer Rate② (65% RH, 73° F)	Moisture Vapor Transfer Rate③ (90% RH, 100° F)	Material	Made In			
				Gallon	Quart	Cups	Liter	Milliliter									
23850	Boil-in Vacuum	In Chamber	6 x 8 (15.2 x 20.3)	.132	.53	2.11	.5	500	212 (100)	4.0	37.2	5.58	Nylon LLDPE Co-ex (Low Density Polyethylene). This material is extruded together during the manufacturing process. BPA free.	U.S.A.			
23852			8 x 12 (20.3 x 30.5)	.475	1.9	7.6	1.8	1800									
23854			12 x 16 (30.5 x 40.6)	1.3	5.7	22.8	5.4	5400									
40815	Vacuum Sealer		8 x 12 (20.3 x 30.5)	.475	1.9	7.6	1.8	1800	158 (70)	3.0	61.8	8.37					
40816			10 x 15 (25.4 x 38.1)	1	4.0	16	3.8	3800									
40817			12 x 16 (30.5 x 40.6)	1.43	5.7	22.8	5.4	5400									
40818			14 x 20 (35.6 x 50.8)	2.86	11.4	45.6	10.8	10800									
40812	Vacuum Sealer - Mesh		Out of Chamber	6 x 12 (15.2 x 30.5)	.2	.85	3.3	.8	800	158 (70)	3.9	75%			85% RH, °73F	PA/PE 20/80 (Polamide and Polyethylene in a 20%80% blend). This is a blend of two materials mixed before the bag is manufactured. BPA free.	Italy
40813				8 x 12 (20.3 x 30.5)	.34	1.4	5.4	1.3	1300								
40814		10 x 14 (25.4 x 35.6)		.63	2.5	10	2.4	2400									

① Capacity is approximate and will vary based on food product  
 ② Oxygen Transfer Rate - cubic centimeter / square meter / 24 hrs  
 ③ Moisture Vapor Transfer Rate - grams / square meter / 24 hrs

Approvals	Date

Due to continued product improvement, please consult [www.vollrath.com](http://www.vollrath.com) for current product specifications.



Outperform every day.™  
[www.vollrath.com](http://www.vollrath.com)

The Vollrath Company, L.L.C.  
 1236 North 18th Street  
 Sheboygan, WI 53081-3201 U.S.A.  
 Customer Service: 800.628.0830  
 Canada Customer Service: 800.695.8560  
 Main Fax: 800.752.5620 or 920.459.6573

Technical Services: 800.628.0832  
 Technical Services Fax: 920.459.5462